

**Maximum realisable performance:
a principled method for enhancing performance by using
multiple classifiers**

M.J.J. Scott, M. Niranjana, D.G. Melvin, R.W. Prager

CUED/F-INFENG/TR. 320

April 1998

Cambridge University Engineering Department
Trumpington Street
Cambridge CB2 1PZ
England
email: mjjs@eng.cam.ac.uk

Maximum realisable performance: a principled method for enhancing performance by using multiple classifiers in variable cost problem domains

M.J.J. Scott, M. Niranjan, D.G. Melvin, R. W. Prager,
Fallside Laboratory
Department of Engineering
University of Cambridge
Trumpington Street
Cambridge, CB2 1PZ
email: `mjjs@eng.cam.ac.uk`

April 1998

Abstract

A novel method is described for obtaining superior classification performance over a variable range of classification costs. By analysis of a set of existing classifiers using a receiver operating characteristic (*ROC*) curve, a set of new *realisable classifiers* may be obtained by a principled random combination of two of the existing classifiers. These classifiers lie on the convex hull that contains the original *ROC* points for the existing classifiers. This hull is the maximum realisable *ROC* (*MRROC*).

A theorem for this method is derived and proved from an observation about *ROC* data, and experimental results verify that a superior classification system may be constructed using only the existing classifiers and the information of the original *ROC* data. This new system is shown to produce the *MRROC*, and as such provides a powerful technique for improving classification systems in problem domains within which classification costs may not be known *a priori* [Lovell *et al.*, 1997b, Lovell *et al.*, 1997a].

1 Introduction

A large fraction of decision support systems, particularly those used in medical diagnostics, are two-class pattern classification systems. Once a set of features and the functions form of the classifier have been chosen, the classifier is designed to optimise some cost function. When the costs of the different types of errors can be specified exactly, the optimum classifier may be designed to minimise the expected risk [Duda and Hart, 1973]. The particular feature set and the functional form chosen then define how well the performance of the classifier approaches the Bayes' performance.

In many real world applications, however, that cost of different types of errors is often not known at the time of designing the classifier. One also finds applications where the costs might change over time. Further, some costs cannot be specified quantitatively. In such situations we resort to specifying the classifier in the form of an adjustable and a receiver operating characteristic (*ROC*) curve obtained by setting the threshold to various possible values. An example of such an *ROC* curve is shown in Figure 1. In the example, the classifier must classify




Figure 1: An *ROC* curve for a medical diagnostic test for abnormal thyroid condition. The true positive rate corresponds to the probability that a sick patient will be diagnosed as sick, the false positive to the probability that a healthy patient will be diagnosed as ill.

a patient's condition as either adverse or benign. The data in the example was obtained from the UCI Machine Learning repository, and represents the results of a number of diagnostic tests for abnormal thyroid conditions. A linear classifier was used, producing a continuous output, and a threshold is placed upon the output to determine the final classification. Two rates can be calculated for

any series of classifications: the true positive and false negative rates. When an adverse case is *correctly* classified as adverse, a true positive has occurred, and a false negative when a benign case is *incorrectly* classified as adverse. By varying the level of the threshold, different degrees of true positive and false positive rates can be achieved, producing the *ROC*.

The *ROC* curve has been shown to be a useful mechanism in comparing the performance of different classifiers [Bradley, 1996, DeLong *et al.*, 1988, Hanley and McNeil, 1983, Lovell *et al.*, 1997b, Halpern *et al.*, 1996, Provost and Fawcett, 1997, Swets and Pickett, 1982]. The area under the *ROC* (*AUROC*) curve is also known as the Wilcoxon statistic [DeLong *et al.*, 1988, Hand, 1997, Hanley and McNeil, 1982, Hanley and McNeil, 1983]. Lovell *et al.*, for example, use this statistic as a criterion for feature selection in a large obstetrics problem involving 48 features and 700,000 cases.

AUROC, however, is a gross simplification of the information conveyed by a *ROC*, as noted in [Hand, 1997]. The costs of different operating points need to be taken into consideration. Hand further suggests this to be an important factor when the *ROC* curves of the classification systems that are being considered cross. Such an example is illustrated in Figure 2




Figure 2: The *ROC* curves of two classification systems cross.

This paper is about combining classifiers to achieve desirable operating points that do not fall on any of the *ROC* curves of the available classification systems. More specifically, we show that a convex hull may be formed, encapsulating the ‘best’ operating points of many classification systems. We provide a theorem to show that an operating point on the convex hull is realisable in practice. We also on an artificially constructed data set, and on the real world thyroid diagnosis data.

2 Realisable classifiers

2.1 An observation about points in ROC space

We think of an *ROC* curve as representing curve joining a set of points in an *ROC* space. A point (fp_c, tp_c) represents an existing classifier c , that classifier producing false positives with a probability $Pr(\text{false positive} = fp_c)$, and true positive with probability $Pr(\text{true positive} = tp_c)$.

Take two classifiers, c_a and c_b , each with distinct false positive and true positive rates. These two classifiers are the end points of a straight line in *ROC* space, L_{ab} . The line L_{ab} defines a set of classifiers, i.e. point $(fp_{c_x}, tp_{c_x}) \in L_{ab}$ represents the classifier that would produce those true positive and false positive rates.

We observe in this paper, that, given only c_a and c_b , one may realise the output of classifier c_x by randomly choosing between the output of c_a and c_b . The probability of choosing the output of c_a over that of c_b is determined by the distance along L_{ab} between c_x and c_a ¹.

Theorem 1 *The realisable classifier. Two existing classifiers, c_a and c_b , produce true positive and false positive rates (tp_a, fp_a) and (tp_b, fp_b) respectively for a series of m inputs $x_1 \dots x_m$. In a 2 dimensional plot of false positive rate against true positive (*ROC* space), call the straight line linking (fp_a, tp_a) and (fp_b, tp_b) L_{ab} .*

Any point (fp_r, tp_r) on L_{ab} corresponds to the point that would be produced by a classifier r . Call the set of classifiers corresponding to n points on L_{ab} , $\mathbf{R} = \{r_1, \dots, r_n\}$.

Given c_a and c_b , the output of a realisable classifier, $r_i \in \mathbf{R}$, for any input x_j , is a random variable that assumes the output of one or other of c_a and c_b with probability

$$\begin{aligned} Pr(r_i(\cdot) = c_b(\cdot)) &= \frac{fp_{r_i} - fp_a}{fp_b - fp_a} \\ Pr(r_i(\cdot) = c_a(\cdot)) &= 1 - Pr(r_i(\cdot) = c_b(\cdot)), \end{aligned}$$

where fp_{r_i} is the false positive rate of r_i .

The proof of Theorem 1 is straightforward. To construct the output of a realisable classifier r_i with false positive rate fp_{r_i} , randomly select between the outputs of c_a and c_b with the given probability. The expected false positive rate produced by doing so is

$$E[fp] = Pr(r_i(\cdot) = c_b(\cdot)) * fp_b + Pr(r_i(\cdot) = c_a(\cdot)) * fp_a$$

¹There exists a parallel to this in classical statistical hypothesis testing [Ferguson, 1967].




Figure 3: An example of a realisable classifier. The point r_i on the line joining c_a and c_b may be realised by the application of Theorem 1

$$\begin{aligned}
&= \frac{fp_{r_i} - fp_a}{fp_b - fp_a} * fp_b + \left(1 - \frac{fp_{r_i} - fp_a}{fp_b - fp_a}\right) * fp_a \\
&= \frac{fp_b(fp_{r_i} - fp_a) + fp_a(fp_{r_i} - fp_a) - fp_a(fp_b - fp_a)}{fp_b - fp_a} \\
&= \frac{(fp_b - fp_a)(fp_{r_i} - fp_a) + fp_a(fp_b - fp_a)}{fp_b - fp_a} \\
&= fp_{r_i} \quad Q.E.D.
\end{aligned}$$

And similarly for the true positive rate.

Figure 3 illustrates an example of a realisable classifier. The realisable classifier r_i , with false positive rate $fp_{r_i} = 0.4$, lies on the line between classifiers c_a and c_b , with false positive rates $fp_a = 0.3$, and $fp_b = 0.5$ respectively. To realise the output of r_i , calculate the probabilities for selecting the outputs of the existing classifiers using Theorem 1,

$$\begin{aligned}
Pr(r_i(\cdot) = c_b(\cdot)) &= \frac{fp_{r_i} - fp_a}{fp_b - fp_a} \\
&= \frac{0.4 - 0.3}{0.5 - 0.3} \\
&= 0.5 \\
Pr(r_i(\cdot) = c_a(\cdot)) &= 1 - Pr(r_i(\cdot) = c_b(\cdot)) \\
&= 0.5.
\end{aligned}$$

To obtain the classification output of r_i on a set of unseen cases, $\mathbf{x} = \{x_1, \dots, x_n\}$,

the classifications of c_a and c_b would be calculated

$$\begin{aligned} c_a(\mathbf{x}) &\rightarrow \{(x_1 = \text{Adverse}), (x_2 = \text{Adverse}), (x_3 = \text{Benign}), \dots, (x_n = \text{Adverse})\} \\ c_b(\mathbf{x}) &\rightarrow \{(x_1 = \text{Benign}), (x_2 = \text{Adverse}), (x_3 = \text{Adverse}), \dots, (x_n = \text{Benign})\}. \end{aligned}$$

Using the probabilities calculated above, the output of r_i is then determined by randomly selecting one of the outputs, like so:

$$\begin{aligned} r_i(\mathbf{x}) &\rightarrow \{c_a(x_1), c_b(x_2), c_a(x_3), \dots, c_b(x_n)\} \\ r_i(\mathbf{x}) &\rightarrow \{(x_1 = \text{Adverse}), (x_2 = \text{Adverse}), (x_3 = \text{Benign}), \dots, (x_n = \text{Benign})\}. \end{aligned}$$

2.2 The maximum realisable *ROC*

We can now realise all classifiers that lie on straight line segments with end points formed by existing classifiers. What advantage can be gained by this? Take the example illustrated in Figure 3. This is the *ROC* produced using a linear model on the 1 dimensional classification problem shown in Figure 4. The steps in the *ROC* occur because the linear model cannot capture the multi modal nature of the data.

We currently have a set of classifiers provided by the linear model, corresponding to the range of false positive rates from 0 to 1. The current *ROC* curve is produced by this set, and can be used to select the best available classifier for a particular false positive rate. It is possible, however, to obtain a new set of classifiers that will give better performance in terms of true positive rates than those provided by the linear model.

Calculate a convex hull [O'Rourke, 1995] such that it contains all the points on the current *ROC*. The vertex points of the convex hull will be points corresponding to existing classifiers generated by the linear model. The facets of the hull are line segments with an existing classifier at each end point. We know from Theorem 1 that all the points on these lines represent realisable classifiers. It is immediately obvious that a realisable classifier r , with false positive rate fp_r , lying on a facet of this hull will have a greater true positive rate than the classifier with false positive rate fp_r found on the original *ROC*.

Given a classification algorithm such as the linear model, and the *ROC* curve produced by this, then the convex hull enclosing this *ROC* represents a set of realisable classifiers that will at all times be either equal or superior to those of the linear model, and that are generated by a subset of the original classifiers. The convex hull describes the maximum realisable *ROC* (*MRROC*) given the available existing classifiers.




Figure 4: Top: an example of 2 class multi modal data. This data will present problems to linear classification systems. Bottom: the *ROC* curve produced by varying the threshold on the output of a linear model of the multi modal data shown. The *ROC* has a step like appearance because the linear model fails to capture the nature of the data.

3 Experimental results

3.1 Artificial data

Multi modal data was generated for the 1 dimensional, 2 class classification problem of Figure 4. A linear model was trained using 5000 training examples. By varying the threshold used on the output of the model when presented with 5000 test cases, the *ROC* curve of Figure 3 was obtained. The true positive rate was the rate of correct classifications of class 1, the false positive rate was the rate of cases of class 2 being incorrectly classified as belonging to class 1..

Using the *qhull* software [Barber *et al.*, 1996] the convex hull containing all the points in the *ROC* was obtained. Each vertex in the hull represented an existing classifier. Each of these existing classifiers was defined by the threshold used, on the output of the linear model, to yield a final classification for each test case. The hypothesis to be tested was that all the points on the facets of the convex hull, corresponding to classifiers that were not currently available,




Figure 5: The convex hull containing the ROC of a linear model is found. This hull is the $MRROC$ of the set of realisable classifiers produced from the set of existing linear classifiers

could be realised by application of Theorem 1 of this paper to the set of vertex classifiers. The $MRROC$ indicates the expected performance, over the complete range of false positive rates, that one might hope to achieve using this approach. Figure 5 plots the $MRROC$ over the ROC of the linear model on the test data.

To validate the hypothesis that the characteristic curve indicated by the $MRROC$ could actually be obtained, a third data set of 5000 validation cases was generated. This validation data was processed by the linear model. The thresholds corresponding to the existing classifiers in the convex hull were each applied to the outputs of the linear model, producing a number of sets of classifications. For any point on a facet of the hull, a classification for an individual validation case could be obtained by randomly selecting one of the classifications made by the two existing classifiers at the end points of the facet. As described above, this methodology leads to the realisation of the set of classifiers on the facets of the hull.

Figure 6 plots the characteristic curve given the set of realisable classifiers indicated with the $MRROC$ against the ROC of the linear model, on the validation data set. It can clearly be seen that the set of realisable classifiers produce an ROC consistent with the $MRROC$, and superior to the ROC of the linear model. The $MRROC$ appears slightly jagged. This is entirely consistent with the nature of the classifiers used to form it. The classifiers are random variables, whose central tendency will be to lie on the $MRROC$.




Figure 6: The *MRROC* plotted for an unseen data set. The *MRROC* is consistent with that predicted.

3.2 Thyroid data

A medical data set describing patients with abnormal thyroid conditions was obtained from the UCI machine learning repository. The data was originally donated by P. Turney, containing 7200 instances, and had three classes, hyperthyroid, hypothyroid, and normal. Each instance had 21 features. For the purpose of this experiment, the hyperthyroid and hypothyroid classes were merged to form the class *Adverse*, and the normal classes kept to form the class *Benign*. The data was randomly split into three data sets, Train, with 3800 instances, Test, with 1700 instances, and Unseen, with 1700 instances.

Two classification systems were made, System 1 and System 2. In each case a simple linear model was trained using a single feature to describe the data. Feature 18 was used for System 1, and feature 19 for System 2. Both systems were tested using the Test data. Figure 7 shows the *ROC* curves for both classification systems using the results on the Test data to calculate the true and false positive rates.

Figure 8 shows the *MRROC* predicted by the convex hull containing the *ROC* points for both systems on the Test data. The vertex points on the hull corresponded, as described in this paper, to existing classifiers. It was required to validate the hypothesis that all the points on the facets of the convex hull were realisable classifiers (by Theorem 1) could be achieved in practice, resulting in the *MRROC*.

The Unseen data set was presented to both System 1 and System 2, and Theorem 1 applied to find the output of the realisable classifiers on the hull. The *ROC* curves for both of the original systems, and for the set of realisable classifiers on the hull are plotted for the Unseen data in Figure 9. It can be

seen that the *ROC* produced by application of Theorem 1 is consistent with the predicted *MRROC*, validating the hypothesis.




Figure 7: The *ROC* curves for both classification systems using the thyroid Test data.

4 Conclusions

This technique for producing enhanced performance given a set of existing classifiers and the *ROC* formed by them may have profound implications for designers of classification systems in domains where classification costs may not be known *a priori*, or may change with time. A principled method for combined multiple classifiers chosen from the *ROC* curves of different classification systems has been described in this paper. It has been shown theoretically that an enhanced performance curve, the *MRROC* can be achieved by application of the realisable classifier theorem, and empirical results provided, on both artificial and real world data, to validate this hypothesis. Given two *ROC* curves that cross, the *MRROC* produced using both will be superior to either alone, and may realise classifiers that were previously unavailable.

The power of this technique is highlighted by the experiment on artificial data, described above. Given the multi modal nature of the data and the linear classifier used, the realisable classifiers lying on the facets of the convex hull represent classification performance that is not possible with the original linear classifier. The gain in performance is not at the expense of clarity or simplicity, nor does it require some degree of expert knowledge to be teased out of the system. The gain is obtained by a clear, simple and principled analysis of the




Figure 8: The convex hull over both original *ROC* curves. This is the predicted *MRROC*.

currently available system (via the *ROC*), and the utilisation of the information acquired by that analysis.

The experiment using thyroid diagnosis data indicates that this method is both applicable and feasible in real world applications.

It is planned to apply this technique to a number of existing medical diagnosis problems, such as those reported in [Lovell *et al.*, 1997b, Lovell *et al.*, 1997a, Melvin, 1996], and to examine the applicability of this methodology to feature selection problems, in the hope that this may produce novel techniques for selecting multiple feature sets across a range of costs. This method will be used to predict the *MRROC* for the liver transplant rejection data described in [Melvin, 1996], and will be included in the blind trial of the various diagnosis systems being considered. It is expected that the *MRROC* will produce a superior diagnosis system than any of the individuals systems alone, thereby justifying its use in real world problem domains.

References

- [Barber *et al.*, 1996] C.B. Barber, D.P. Dobkin, and H.T. Huhdanpaa. The quick-hull algorithm for convex hulls,. *ACM Transactions on Mathematical Software*, 22(4):469–483, 1996.
- [Bradley, 1996] A. Bradley. *PhD Thesis : Machine learning for medical diagnostics*. Ph. D. thesis, Dept Electrical and Computer Engineering, University of Queensland, Australia, 1996.




Figure 9: The *MRROC* plotted for the Unseen data set. The *MRROC* is consistent with that predicated by the convex hull over the Test data *ROC* curves. The *ROC* curves for System 1 and System 2 using the Unseen data are plotted for comparison with the *MRROC*.

- [DeLong *et al.*, 1988] E.R. DeLong, D.M. DeLong, and D.L. Clarke-Pearson. Comparing the areas under two or more correlated receiver operating characteristic curves: a non parametric approach. *Biometrics*, 44(11):837–845, 1988.
- [Duda and Hart, 1973] R.H. Duda and P.E. Hart. *Pattern classification and scene analysis*. Wiley, 1973.
- [Ferguson, 1967] T.S. Ferguson. *Mathematical Statistics, a Decision Theoretic Approach*. Academic Press, 1967.
- [Halpern *et al.*, 1996] E.J. Halpern, M.A. Albert, A.M. Krieger, C.E. Metz, and A.D. Maidment. Comparison of receiver operating characteristic curves on the basis of optimal operating points. *Academic Radiology*, 3(3):245–253, 1996.
- [Hand, 1997] D.J. Hand. *Construction and Assessment of Classification Rules*. Wiley, 1997.
- [Hanley and McNeil, 1982] J.A. Hanley and B.J. McNeil. The meaning and use of the area under a receiver operating characteristic (roc) curve. *Radiology*, 82(143):29–36, 1982.
- [Hanley and McNeil, 1983] J.A. Hanley and B.J. McNeil. A method of comparing the areas under receiver operating characteristic curves derived from the same cases. *Radiology*, 83(148):839–843, 1983.

- [Lovell *et al.*, 1997a] D.R. Lovell, B. Rosario, M. Niranjana, R.W. Prager, K.J. Dalton, R. Derom, and J. Chalmers. Design, construction and evaluation of systems to predict risk in obstetrics. *International Journal of Medical Informatics*, 46(3):159–173, 1997.
- [Lovell *et al.*, 1997b] D.R. Lovell, M.J.J. Scott, M. Niranjana, R.W. Prager, and K.J. Dalton. On the use of expected attainable discrimination for feature selection in large scale medical risk prediction problems. Technical Report CUED/F-INFENG/TR.299, Department of Engineering, University of Cambridge, England, August 1997.
- [Melvin, 1996] D.G. Melvin. A comparison of statistical and connectionist techniques for liver transplant monitoring. Technical Report CUED/F-INFENG/TR.282, Department of Engineering, University of Cambridge, England, December 1996.
- [O’Rourke, 1995] J. O’Rourke. *Computational Geometry in C*. Cambridge University Press, 1995.
- [Provost and Fawcett, 1997] F. Provost and T. Fawcett. Analysis and visualisation of classifier performance: comparison under imprecise class and cost distributions. In *Proceedings of the Third International Conference on Knowledge Discovery and Data Mining*. American Association for Artificial Intelligence, 1997.
- [Swets and Pickett, 1982] J.A. Swets and R.M. Pickett. *Evaluation of Diagnostic Systems*. Academic Press, 1982.